

Specifications

DESCRIPTION	NORM	DATA
Type de revêtement / Type of flooring		Aiguilleté plat en dalle 2*1m/ Flat needlefelt in tile 2*1m
Type d'enduction / Type of bonding		Enduction d'envers / Back coated
Composition des fibres de surface / Fiber composition of surface		40% Polyamide dorig®, 40% Polypropylène, 20% Polyester
Masse totale de surface / Total weight of surface	ISO 8543	600 g/m ²
Masse totale / Total Weight	ISO 8543	4330 g/m ²
Epaisseur totale / Total Thickness	ISO 1765	6,0 mm
Envers / Backing		Matières recyclées renforcées par un voile de verre / Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Dimensions / Tile Size		200x100 cm
Dalles par boîte / Tiles per Box		
Sens de pose / Installation		

Technical performances



Classification EN 1307 - 33 / Commercial Heavy

Luxury Class - LC1



Feu / Fire rating EN 13501-1 : Bfl-s1



				RHO - LRV	
				9 colors	
 Heated Floor ISO 10456 0,08 m ² K/W	 Impact noise reduction EN ISO 10143-3 ΔL _(w) 19 dB	911			
		912			
 Castor Chair EN 985 Passed R ≥ 2,4	 Sound absorption ISO 11654 α _w = 0,15 (H)	913			
		914			
 Dimensional Stability EN 986 ≤ 0,10%	 Colour Fastness EN 105 - B02 ≥ 6/8	915			
		916			
 N° 0679-CPR-0200 11 EN 14041 : 2004	 Electrostatic prop. ISO 6356 ≤ 2,0kV ISO 10965 RT ≈ 10 ¹⁰ Ω Propriété Antistatique / Antistatic Property	917			
		918			
		919			

Environmental issues

LEED

