


Specifications

DESCRIPTION	DATA	NORM
Type de revêtement / Type of flooring	Dalle Plombante Amovible (DPA) touffetée / Tufted loose lay Tile	
Composition fibreuse / Pile Fibre	100% ECONYL (Teint masse / Solution dyed)	
Jauge / Gauge	1/10 loop pile	
Densité / Tuft Density	168 800 Stitches/m ²	ISO 1763
Poids de fil / Total pile mass	540 g/m ²	ISO 8543
Masse de velours utile / Mass of pile above the substrate	370 g/m ²	ISO 8543
Epaisseur velours utile / Thickness of pile above the substrate	3,4 mm	ISO 1766
Densité du velours de surface / Surface pile density	0,108 g/cm ³	ISO 8543
Masse totale / Total Weight	3650g/m ²	ISO 8543
Epaisseur totale / Total Thickness	10,4 mm	ISO 1765
Premier dossier / Primary Backing	Non tissé / Non woven primary backing	
Envers / Backing	Fibres synthétiques 100% recyclées 100% recycled fibers	
Dimensions / Tile Size	50x50cm	
Dalles par boîte / Tiles per Box	16 = 4m ²	
Sens de pose / Installation		


RHO - LRV

22 colors	%
022	14,5%
026	3,0%
027	3,8%
028	3,2%
032	27,0%
035	18,4%
038	6,2%
045	7,5%
055	11,3%
062	23,9%
074	12,5%
077	9,0%
081	22,0%
084	16,0%
087	4,7%
096	5,8%
104	30,4%
106	17,6%
115	5,1%
149	1,9%
155	8,0%
224	10,7%

Technical performances









Classe de confort / Luxury Class - LC1



Classe d'usage / Overall use class (Classification EN 1307) - 23/33 / Commercial Heavy

Classement feu / Fire rating (EN 13501-1): Bfl-s1



Heated Floor  ISO 10456 0,14 m ² K/W	Castor Chair  EN 985 Passed R>3,4
Electrostatic prop.  ISO 6356 <2,0 kV ISO 10965 RT ≈ 10 ¹⁰ Ω	Colour Fastness  EN 105 - B02 ≥ 5/8
Dimensional Stability  EN 986 < 0,20%	Impact noise reduction  EN ISO 10143-3 ΔL _(w) 27 dB
 N° 0679-CPR-1316 EN 14041 : 2004 +AC: 2006	Sound absorption  ISO 11654 α _w =0,30 125Hz 250Hz 500Hz 1000Hz 2000Hz 4000Hz 0,03α _s 0,07α _s 0,53α _s 0,21α _s 0,29α _s 0,38α _s

Environmental issues
