



Specifications

DESCRIPTION	DATA	NORM
Type de revêtement / Type of flooring	Dalle Plombante Amovible (DPA) touffetée / Tufted loose lay Tile	
Composition fibreuse / Pile Fibre	100% Polyamide (Teint masse/Solution dyed)	
Jauge / Gauge	5/64 loop pile	
Densité / Tuft Density	213 200 Stitches	ISO 1763
Poids de fil / Total pile mass	725 g/m ²	ISO 8543
Masse de velours utile / Mass of pile above the substrate	370 g/m ²	ISO 8543
Epaisseur velours utile / Thickness of pile above the substrate	2,9 mm	ISO 1766
Densité du velours de surface / Surface pile density	0,128 g/cm ³	ISO 8543
Masse totale / Total Weight	3869g/m ²	ISO 8543
Epaisseur totale / Total Thickness	9,8 mm	ISO 1765
Premier dossier / Primary Backing	Non tissé / Non woven primary backing	
Envers / Backing	Fibres synthétiques 100% recyclées / 100% recycled fibers	
Dimensions / Tile Size	50x50cm	
Dalles par boîte / Tiles per Box	16 = 4m ²	
Sens de pose / Installation		Pose effet dégradé / shading off effect
Base d'impression / Printing facilities	YES DESIGN FACILITIES	

Technical performances

Classe de confort / Luxury Class - LC1
 Classe d'usage / Overall use class (Classification EN 1307) - 23/33 / Commercial Heavy
 Classement feu / Fire rating (EN 13501-1): Bfl-s1

						9 colors		
	ISO 10456	0,13 m ² K/W		EN 985	Passed R>3,4	130		
							131	
	ISO 6356	< 2,0kV		EN 105 - B02	7/8	139		
	ISO 10965	RT \geq 10 ¹⁰ Ω					182	
	EN 986	< 0,20%		EN ISO 10143-3	ΔL _(w) 26 dB	239		
							302	
	N° 0679-CPR-1316			ISO 11654	α _w = 0,25	303		
	EN 14041 : 2004 +AC: 2006						309	
				125Hz 250Hz 500Hz 1000Hz 2000Hz 4000Hz 0,01α _s 0,06α _s 0,48α _s 0,19α _s 0,25α _s 0,33α _s			479	

Environmental issues



Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.