



Specifications

DESCRIPTION	DATA	NORM
Type de revêtement / Type of flooring	Dalle Plombante Amovible (DPA) touffetée / Tufted loose lay Tile	
Composition fibreuse / Pile Fibre	100% Polyamide (Teint masse/Solution dyed)	
Jauge / Gauge	1/10 loop pile	
Densité / Tuft Density	143 500 Stitches/m ²	ISO 1763
Poids de fil / Total pile mass	510 g/m ²	ISO 8543
Masse de velours utile / Mass of pile above the substrate	300 g/m ²	ISO 8543
Epaisseur velours utile / Thickness of pile above the substrate	3.0 mm	ISO 1766
Densité du velours de surface / Surface pile density	0,100 g/cm ³	ISO 8543
Masse totale / Total Weight	3588 g/m ²	ISO 8543
Epaisseur totale / Total Thickness	10 mm	ISO 1765
Premier dossier / Primary Backing	Non tissé / Non woven primary backing	
Envers / Backing	Fibres synthétiques 100% recyclées / 100% recycled fibers	
Dimensions / Tile Size	50x50cm	
Dalles par boîte / Tiles per Box	16 = 4 m ²	
Sens de pose / Installation		

Technical performances

Classe de confort / Luxury Class - LC1



Classe d'usage / Overall use class (Classification EN 1307) - 23/33 / Commercial Heavy

Classement feu / Fire rating (EN 13501-1): Bfl-s1



 Heated Floor ISO 10456 0,14 m ² K/W	 Castor Chair EN 985 Passed R≥3,3	RHO - LRV	
		4 colors	%
 Electrostatic prop. ISO 6356 ≤ 2,0kV	 Colour Fastness EN 105 - B02 7/8	925	6,4%
		936	10,7%
 Dimensional Stability EN 986 ≤ 0,20%	 Impact noise reduction EN ISO 10143-3 ΔL _(w) 27 dB	937	9,8%
		997	6,0%
 N° 0679-CPR-1316 EN 14041 : 2004 +AC: 2006	 Sound absorption ISO 11654 α _w = 0,30 (H) 125Hz 250Hz 500Hz 1000Hz 2000Hz 4000Hz 0,00α□ 0,10α□ 0,35α□ 0,25α□ 0,30α□		

Environmental issues



Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.

Mise à jour/Updated on 23/06/2020