

Specifications

DESCRIPTION	NORM	DATA
Composition fibreuse / Pile Fibre		100% Polyamide (Teint masse/Solution dyed)
Jauge / Gauge		5/64e loop pile
Densité / Tuft Density	ISO 1763	223 600 Stitches/m ²
Poids de fil / Total pile mass	ISO 8543	885 g/m ²
Masse de velours utile / Mass of pile above the substrate	ISO 8543	500 g/m ²
Epaisseur velours utile / Thickness of pile above the substrate	ISO 1766	4 mm
Densité du velours de surface / Surface pile density	ISO 8543	0,125 g/cm ³
Masse totale / Total Weight	ISO 8543	5545 g/m ²
Epaisseur totale / Total Thickness	ISO 1765	10,5 mm
Premier dossier / Primary Backing		Non tissé / Non woven primary backing
Envers / Backing		Matières recyclées renforcées par un voile de verre / Vinyl backing reinforced with glass fiber (100 % recycled PVC) Renfort acoustique avec fibres synthétiques 100% recyclées / Acoustic reinforcement with 100% recycled fibers
Dimensions / Tile Size		50x50cm
Dalles par boîte / Tiles per Box		16 = 4 m ²
Sens de pose / Installation		

Technical performances



Classification EN 1307 - 33 / Commercial Heavy
Luxury Class - LC2



Feu / Fire rating EN 13501-1 : Bfl-s1



		RHO - LRV	
		10 colors	%
	ISO 10456 0,14 m ² K/W	030	14,8%
	ISO 6356 ≤ 2,0kV ISO 10965 RT ≈ 10 ¹⁰ Ω	130	24,0%
	EN 986 ≤ 0,10%	139	14,8%
	N° 0679-CPR-1149 17 EN 14041 : 2004	140	9,2%
	EN ISO 10143-3 ΔL _(w) 30 dB	171	23,7%
	ISO 11654 α _w = 0,30 (H)	182	28,6%
	EN 105 - B02 7/8	209*	11,0%
	EN 985 Passed R≥2,4	230	18,5%
		240	12,6%
		340	7,4%

Environmental issues

LEED

Répond à la démarche
HQE

