

## Specifications

DESCRIPTION	NORM	DATA
Type de revêtement / Type of flooring		Aiguilleté imprimé plat en dalle (DPA) /Printed flat needlefelt in tile (loose lay tile)
Type d'enduction / Type of bonding		Enduction d'envers / Back coated
Composition des fibres de surface / Fiber composition of surface		100% Polyamide
Masse totale de surface / Total weight of surface	ISO 8543	400 g/m <sup>2</sup>
Masse totale / Total Weight	ISO 8543	4300 g/m <sup>2</sup>
Epaisseur totale / Total Thickness	ISO 1765	6,1 mm
Envers / Backing		Matières recyclées renforcées par un voile de verre / Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Dimensions / Tile Size		50x50cm
Dalles par boîte / Tiles per Box		20 = 5m <sup>2</sup> - 120 m <sup>2</sup> par palette / by pallet
Sens de pose / Installation		

## Technical performances



Classification EN 1307 - 33 / Commercial Heavy  
Luxury Class - LC1



Étanche à l'eau EN 1307 / Water Resistant



Résistant aux taches  
Feu / Fire rating EN 13501-1 : BflS1



		RHO - LRV	
		12 colors	%
		<b>POP 3 - 416530505-00XXX</b>	
		012	22,6%
		052	28,7%
		083	20,6%
		113	21,6%
		<b>POP 5 - 416540505-00XXX</b>	
		015	15,7%
		018	10,3%
		032	24,9%
		055	20,5%
		084	20,4%
		088	15,0%
		115	15,9%
		117	11,1%

  

<b>Heated Floor</b> 	ISO 10456	0,08 m <sup>2</sup> K/W	<b>Impact noise reduction</b> 	EN ISO 10143-3	$\Delta L_{(w)}$ 20 dB
<b>Castor Chair</b> 	EN 985	Passed R $\geq$ 2,4	<b>Sound absorption</b> 	ISO 11654	$\alpha_w = 0,15$ (H)
<b>Dimensional Stability</b> 	EN 986	$\leq 0,20\%$	<b>Colour Fastness</b> 	EN 105 - B02	$\geq 5/8$
<b>CE</b>	0679-CPR-1232	18	<b>Electrostatic prop.</b> 	ISO 6356	$\leq 2,0kV$
	EN 14041 : 2004			ISO 10965	RT $\approx 10^{10}\Omega$
			Propriété Antistatique / Antistatic Property		

## Environmental issues

# LEED



Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.