

Specifications

DESCRIPTION	NORM	DATA
Type de revêtement / Type of flooring		Dalle Plombante Amovible (DPA) touffetée / Tufted loose lay Tile
Composition fibreuse / Pile Fibre		100% Polyamide (Teint masse/Solution dyed)
Jauge / Gauge		5/64e loop pile
Densité / Tuft Density	ISO 1763	223 600 Stitches/m ²
Poids de fil / Total pile mass	ISO 8543	845g/m ²
Masse de velours utile / Mass of pile above the substrate	ISO 8543	500 g/m ²
Épaisseur velours utile / Thickness of pile above the substrate	ISO 1766	4 mm
Densité du velours de surface / Surface pile density	ISO 8543	0,125 g/cm ³
Masse totale / Total Weight	ISO 8543	4160 g/m ²
Épaisseur totale / Total Thickness	ISO 1765	7,3 mm
Premier dossier / Primary Backing		Non tissé / Non woven primary backing
Envers / Backing		Matières recyclées renforcées par un voile de verre Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Dimensions / Tile Size		50x50cm
Dalles par boîte / Tiles per Box		20 = 5m ²
Sens de pose / Installation		

Technical performances



Classification EN 1307 - 33 / Commercial Heavy
Luxury Class - LC2



Feu / Fire rating EN 13501-1 : Bfl-S1

		RHO - LRV	
		9 colors	%
 Heated Floor ISO 10456 0,10 m ² K/W	 Impact noise reduction EN ISO 10143-3 ΔL _(w) 26 dB	100	4,14%
		130	21,97%
 Electrostatic prop. ISO 6356 ≤ 2,0kV ISO 10965 RT ≈ 10 ¹⁰ Ω	 Sound absorption ISO 11654 α _w = 0,15 (H)	140	1,26%
		231	8,49%
 Dimensional Stability EN 986 ≤ 0,10%	 Colour Fastness EN 105 - B02 7/8	309	3,24%
		470	31,58%
 N° 0679-CPR-0196 17 EN 14041 : 2004	 Castor Chair EN 985 Passed R _{≥2,4}	591	1,90%
		592	7,53%
		930	11,25%

Environmental issues

LEED

Répond à la démarche
HQE



Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.