





Specifications

DESCRIPTION	NORM	DATA
Type de revêtement / Type of flooring		Dalle Plombante Amovible (DPA) touffetée /Tufted loose lay Tile
Composition fibreuse / Pile Fibre		100% Polyamide (50% Teint masse/Solution dyed + 50% structure teinte fils ECONYL/space dyed ECONYL Yarns)
Jauge / Gauge		1/10 loop pile
Densité / Tuft Density	ISO 1763	151 700 Stitches/m ²
Poids de fil / Total pile mass	ISO 8543	520 g/m ²
Masse de velours utile / Mass of pile above the substrate	ISO 8543	290 g/m ²
Epaisseur velours utile / Thickness of pile above the substrate	ISO 1766	2.9 mm
Densité du velours de surface / Surface pile density	ISO 8543	0,100 g/cm ³
Masse totale / Total Weight	ISO 8543	4300 g/m ²
Epaisseur totale / Total Thickness	ISO 1765	6.8 mm
Premier dossier / Primary Backing		Non tissé / Non woven primary backing
Envers / Backing		Matières recyclées renforcées par un voile de verre Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Dimensions / Tile Size		50x50cm
Dalles par boîte / Tiles per Box		20 = 5m ²
Sens de pose / Installation		

Technical performances



Classification EN 1307 - 23/32 / Commercial General










Luxury Class - LC1



Classement UPEC QB 31 - U₃P₃E₁C₀ (certificat n° 349T-002.1)

Feu / Fire rating EN 13501-1 : BflS1



Heated Floor		Impact noise reduction		RHO - LRV	
	ISO 10456 0,09 m ² K/W		EN ISO 10143-3 ΔL _(w) 24 dB	5 colors	%
	ISO 6356 ≤ 2,0kV		ISO 11654 α _w = 0,15 (H)	034	14,1%
	ISO 10965 RT ≈ 10 ¹⁰ Ω		EN 105 - B02 ≥ 5/8	038	7,7%
	EN 986 ≤ 0,10%		EN 985 Passed R _{≥2,4}	045	7,0%
	N° 0679-CPR-0196			068	14,1%
	07			428	4,6%
	EN 14041 : 2004				

Environmental issues



Les informations ci-dessus peuvent subir des modifications au profit d'une future amélioration / The above information is subject to modifications for the benefit of further improvement.